



Features

- f/2 aperture
- Moderate wide-angle lens
- Precise manual focusing
- Robust full-metal construction
- Fixation for focus and aperture
- Outstanding image quality
- Compact and lightweight
- For industrial cameras up to sensor sizes of 24x36 mm or 43mm line sensors.

M42-I: Industrial Edition

Features special screws to fix focus and aperture settings even in rough situations.

Camera Mount

Available with M42-Mount.



Technical Specifications



Focal length	35 mm
Aperture range	f/2 – f/22 (1/ 3 stop intervals)
Number of elements / groups	9/6
Focusing rage	0.7 m - ∞
Min. free working distance	630 mm (2.07 ft.)
Angular field* (diag. / horiz. / vert.)	63 / 54 / 38°
Max. diameter of image field	43 mm (1.7")
Flange focal distance	M42-I: 26.8 mm
Coverage at close range*	43 x 65 cm
Image ratio at close range	1:18
Filter-thread	M 43 x 0.75
Weight	240 g (0.53 lbs)
Length	56 mm
Camera mount	M42-I

* referring to 24x36mm sensor format



Relative Illuminance*



The relative illumination shows the decrease in image brightness from the image center to the edge in percent.

____ f-number 2.0 ... f-number 4.0

Relative Distortion*



The relative distortion shows the deviation of the actual image height from the ideal one in percent.

* data for infinite focus setting



MTF Charts*

MTF [%] k=2.0



The Modulation Transfer (MTF) as a function of image height (u) and slit orientation (sagittal, tangential) has been measured with white light at spatial frequencies of R = 10, 20 and 40 cycles/mm. The MTF charts are valid for the ZM-version and for white light.

f-number 2.0 ____SagittalTangential



* data for infinite focus setting

f-number 4.0 ___ Sagittal ... Tangential