





#### Features

- Very fast f/1.4 aperture
- Precise manual focusing
- Robust full-metal construction
- Continuous aperture setting or click stop
- For industrial cameras up to sensor sizes of 24x36 mm or 41 mm line sensors
- High optical performance both at infinity and at 1:4.6 scale
- Features special screws to fix focus and aperture settings even in rough situations

**Camera Mounts** Available with F mount or M42 screw mount



### **Technical Specifications**



Focal length	25 mm
Aperture range	f/1.4 – f/16 (1/ 2 stop intervals or continuous)
Number of elements / groups	15 / 13
Min. working distance	252 mm (0.83 ft.) – ∞
(object to sensor)	
Min. free working distance	93 mm (0.31 ft.) — ∞
Angular field* (diag. / horiz. / vert.)	81,2° / 70,8° / 50,4°
Max. diameter of image field	43 mm (1.69")
Flange focal length	F-Mount: 46,5 mm (1.8");
	M42-Mount: 45,5 mm
Coverage at close range*	area: 166 x 110 mm (6.5″ x 4.3")
	line: 188 mm (7,4")
Image ratio at close range	1 : 4.6
Filter-thread	M82 x 0.75
Weight	1.218 g (2.7 lbs.)
Camera mount	F bayonet, M42



#### **Relative Illuminance\***

E [%]

The relative illumination shows the decrease in image brightness from the image center to the edge in percent.

\_\_\_ f-number 1.4 --- f-number 4

#### **Relative Distortion\***



The relative distortion shows the deviation of the actual image height from the ideal one in percent.

\*Data for infinite focus setting



#### **MTF Charts\***





\*Data for infinite focus setting



### **Spectral Transmission**







The diameter of the camera/lens adapter must not exceed 55 mm at the lens side!