

Vibration Resistant Distortionless Lens

Model		VS-MCA35								
Focal Length(f)		35 mm (35.04)								
Maximum Aperture Ratio		1: 1.9								
Optical Mag. Range		× 0.26 ~ × 0.65								
Optical Mag.		× 0.26			× 0.45			× 0.65		
FOV (V x H)	2/3"	27.3 × 32.3 mm			15.8 × 18.7 mm			10.9 × 12.9 mm		
	1/2"	18.5 × 24.6 mm			10.7 × 14.2 mm			7.4 × 9.9 mm		
	1/3"	13.9 × 18.5 mm			8.0 × 10.7 mm			5.5 × 7.4 mm		
WD		163.9 mm			107.0 mm			83.1 mm		
O/I (Object & Imager Distance)		213.4 mm			163.2 mm			146.3 mm		
Aperture		1.9	5.6	8	1.9	5.6	8	1.9	5.6	8
Working F/#		2.5	7.1	10.1	3.0	8.1	11.6	3.5	9.2	13.2
TV Distortion (2/3")		0.03 %			0.00 %			0.01 %		
Operation		Manual								
Wavelength		Visible								
Mount		C-Mount								
Flange Back		17.526 mm								
Sensor Size (max.)		2/3"								
Filter Thread		M 27 P= 0.5								
Weight (approx.)		43 g								
Dimension		φ 31 (max.) × L = 32 (X0.26) ~ 45.7 (X0.65) mm								

※ Note: Available with MC Focus Locking System, FNO (Iris Open) 5 .6 & 8