

LXC-250C

Camera Link®, 25 Megapixel, Color

Article number: 11162827

Overview

- 5120 × 5120 px
- ON Semiconductor PYTHON 25K
- APS-H CMOS
- 32 fps
- Camera Link® Full
- available



GEN*i*CAM



Technical data

Sensor information

Sensor	ON Semiconductor PYTHON 25K
Resolution	5120 × 5120 px
Exposure time	0,03 ... 1000 ms
Color filter	RGB Bayer Mosaic
Pixel size	4.5 × 4.5 µm
Shutter type	Global shutter
Sensor type	APS-H CMOS

Acquisition formats

Image formats, interface frame rate max.	Full Frame, 5120 × 5120 px, max. 32 fps
Pixel formats	BayerGB8 BayerGB10

Image preprocessing

Analog controls	Gain (0 ... 23,5 dB) Offset (0 ... 63 LSB 10 Bit)
Color models	Raw Bayer
Color processing	NA

Camera features

Synchronization	free running trigger
Trigger sources	Hardware Software ActionCommand
Trigger delay	0 ... 2 sec, tracking and buffering of up to 256 trigger signals
Sequencer	Automated control for series of images using different sets of parameters

Camera features

Sequencer parameter	Exposure time gain factor Output ROI Offset x ROI Offset y
Digital inputs	1 input line
Digital outputs	1 output line
Internal image buffer	512 MB

Interfaces and connectors

Data interface	Camera Link Full, connector: 2 x Standard SDR26 (Mini CL)
Process interface	M8 / 8 pins
Power supply	via M8 / 8 pins

Mechanical data

Lens mount	M58-mount (F-mount, M42, C-mount via adapter)
Width	60 mm
Height	60 mm
Depth	45,12 mm
Weight	≤ 235 g (M58-mount)
Material	housing: aluminum

Electrical data

Voltage supply range +Vs	12 ... 24 V DC (external power supply) 38 ... 57 V (PoCL)
Power consumption	approx. 7,8 W @ 24 VDC approx. 7,8 W @ 12 VDC (PoCL)

LXC-250C

Camera Link®, 25 Megapixel, Color

Article number: 11162827

Technical data

Non-volatile memory

Flash memory size 128 kB

Environmental conditions

Operating temperature +5 ... +66 °C @ T = measurement point

Humidity 10 ... 90 % (non-condensing)

Environmental conditions

Protection class IP 40

Conformity

Conformity CE
RoHS
EAC

Dimension drawing

