

## LXC-250M

Camera Link®, 25 Megapixel, Monochrome

Article number: 11162825

### Overview

- 5120 × 5120 px
- ON Semiconductor PYTHON 25K
- APS-H CMOS
- 32 fps
- Camera Link® Full
- available



GEN*i*CAM



### Technical data

#### Sensor information

Sensor	ON Semiconductor PYTHON 25K
Resolution	5120 × 5120 px
Exposure time	0,03 ... 1000 ms
Pixel size	4.5 × 4.5 µm
Shutter type	Global shutter
Sensor type	APS-H CMOS

#### Acquisition formats

Image formats, interface frame rate max.	Full Frame, 5120 × 5120 px, max. 32 fps Binning 2×2, 2560 × 2560 px, max. 32 fps Binning 1×2, 5120 × 2560 px, max. 32 fps Binning 2×1, 2560 × 5120 px, max. 32 fps
Pixel formats	Mono8 Mono10

#### Image preprocessing

Analog controls	Gain (0 ... 23,5 dB) Offset (0 ... 63 LSB 10 Bit)
Color models	Mono

#### Camera features

Synchronization	free running trigger
Trigger sources	Hardware Software ActionCommand
Trigger delay	0 ... 2 sec, tracking and buffering of up to 256 trigger signals
Sequencer	Automated control for series of images using different sets of parameters

#### Camera features

Sequencer parameter	Exposure time gain factor Output ROI Offset x ROI Offset y
Digital inputs	1 input line
Digital outputs	1 output line
Internal image buffer	512 MB

#### Interfaces and connectors

Data interface	Camera Link Full, connector: 2 x Standard SDR26 (Mini CL)
Process interface	M8 / 8 pins
Power supply	via M8 / 8 pins

#### Mechanical data

Lens mount	M58-mount (F-mount, M42, C-mount via adapter)
Width	60 mm
Height	60 mm
Depth	45,12 mm
Weight	≤ 235 g (M58-mount)
Material	housing: aluminum

#### Electrical data

Voltage supply range +Vs	12 ... 24 V DC (external power supply) 38 ... 57 V (PoCL)
Power consumption	approx. 7,8 W @ 24 VDC approx. 7,8 W @ 12 VDC (PoCL)

## LXC-250M

Camera Link®, 25 Megapixel, Monochrome

Article number: 11162825

### Technical data

#### Non-volatile memory

Flash memory size 128 kB

#### Environmental conditions

Operating temperature +5 ... +66 °C @ T = measurement point

Humidity 10 ... 90 % (non-condensing)

#### Environmental conditions

Protection class IP 40

#### Conformity

Conformity CE  
RoHS  
EAC

### Dimension drawing

