

LDL2 Series

Direct Illumination Bar Lights

Patented

Design Registered

Wide Range of Variations

A Total of **277** Models

Wide Product Lineup with 277 Variations

* Includes customized products.



A Total of 277 Models

The standard LDL2 Series lineup includes 61 models with a light-emitting surface from a compact 33 mm × 8 mm to a wide 266 mm × 30 mm. In addition, up to 216 customized models are available. Various combinations of size, color, and directional characteristics can be selected from a total of 277 models.

Models with 16-mm-wide Light-emitting Surface

Sizes Light-emitting surface: 41 mm Up to 509 mm max. 16 mm Standard products Special order <table border="1"> <tr> <td>41</td><td>80</td><td>119</td><td>158</td><td>197</td><td>236</td><td>275</td><td>314</td><td>353</td></tr> <tr> <td>392</td><td>431</td><td>470</td><td>509</td><td></td><td></td><td></td><td></td><td></td></tr> </table> 13 sizes	41	80	119	158	197	236	275	314	353	392	431	470	509						Light Color Red White Blue Green 4 colors	Directional Characteristics Narrow type Wide type 2 types	Total of 104 models
41	80	119	158	197	236	275	314	353													
392	431	470	509																		

Models with 30-mm-wide Light-emitting Surface

Sizes Light-emitting surface: 26 mm Up to 506 mm max. 30 mm Standard products Special order <table border="1"> <tr> <td>26</td><td>50</td><td>74</td><td>98</td><td>122</td><td>146</td><td>170</td><td>194</td><td>218</td></tr> <tr> <td>242</td><td>266</td><td>290</td><td>314</td><td>338</td><td>362</td><td>386</td><td>410</td><td>434</td></tr> <tr> <td>458</td><td>482</td><td>506</td><td></td><td></td><td></td><td></td><td></td><td></td></tr> </table> 21 sizes	26	50	74	98	122	146	170	194	218	242	266	290	314	338	362	386	410	434	458	482	506							Light Color Red White Blue Green 4 colors	Directional Characteristics Narrow type Wide type 2 types	Total of 168 models
26	50	74	98	122	146	170	194	218																						
242	266	290	314	338	362	386	410	434																						
458	482	506																												

Models with 8-mm-wide Light-emitting Surface


Sizes Light-emitting surface: 33 mm 8 mm Standard products 1 size	Light Color Red White Blue Green Infrared 5 colors	Directional Characteristics Wide type 1 type	Total of 5 models
--	---	---	---------------------------------

Models with Either Narrow and Wide Directional Characteristics Can Be Selected

Two types of models are available with different directional characteristics: narrow models, which use an original lens, and wide models, which have diffuse illumination over a wide range.

Directional Characteristics of Narrow Models


Enlargement of Light-emitting Surface



* Actual measurement using a model with 16-mm-wide light-emitting surface

Directional Characteristics of Wide Models

Enlargement of Light-emitting Surface




* Actual measurement using a model with 16-mm-wide light-emitting surface

Free Selection of Mounting to Match Your Site Environment

You can select from two methods for greater mounting versatility to match your installation environments: frame structure mounting or tapped mounting holes.

Brackets for which you can adjust the angle of irradiation are available to mount the Light Units.



The cable lies flat to the mounting surface, and so mounting can be made to any surface.


With frame structure mounting, the lighting position and mounting location can be adjusted by sliding the mounting nuts into the internal grooves in the frame structure.

* The LDL2-33×8 Series provides only tap holes for installation.

BK-LDL2




The angle of irradiation can be adjusted for a variety of methods, such as for parallel emission from two directions.



BK-LDQ2 series



The angle of irradiation can be adjusted when using surrounding emission from four directions.



High-efficiency Heat Dissipation

The heat radiating fins and the frame structure significantly increases the surface area. This improves the efficiency of heat dissipation and reduces the rise in temperature of the LED mounting section. This heat dissipation structure reduces the strain on the LEDs and enables a long and stable performance of the Light Unit.

Common Power Supply for All Colors

The same power supply can be used for all Light Units regardless of color. Although previously 12 V was used only for red light, the voltage is now 24 V for all colors.

The Compact LDL2-33×8 Helps You Save Space

Lightweight, compact designs lend themselves to installation in tight equipment spaces, contributing to saving space onsite.


Features

- The LDL2-33×8-series Compact Bar Light Units have a lightweight and compact design weighing only 20 g.
- Infrared light is also available in addition to red, white, blue, and green light.
- Diffusion Plates and Polarizing Plates are available.
- Wide-type directional characteristics are provided.
- Use the tap holes on the ends or on the back for mounting. A special bracket is also available.

BK-LDQ2-33×8 Bracket





Directional Characteristics



Application Examples

Bar Light Units can be used to supplement other illumination devices and can be installed in small spaces.



Supported Options

Diffusion Plates, Polarizing Plates, and Protective Plates of various sizes are available. They can be easily mounted by inserting them in the grooves on the sides of the Light Units. Brackets for which you can adjust the angle of irradiation are also available.

* The LDL2-33×8-series Bar Light Units are mounted with screws.

Diffusion Plate **DF-LDL2 Series**



The irradiated light is diffused to suppress workpiece glare and reflections.

* This option is not effective with infrared light.

Polarizing Plate **PL-LDL2 Series**



This plate polarizes the light. Prevent light reflection by using the Polarizing Plate together with the Polarizing Filter (PL Series) mounted to the lens.

* This option is not effective with infrared light.

Protective Plate **CV-LDL2 Series**



This cover shields the light-emitting portion.

* It is not intended to protect the surface from dust or water droplets.

* Cannot be used with the LDL2-33×8 Series.

Bracket **BK-LDL2 (for All Series)**



You can adjust the irradiation angle when you secure the Light Unit.

* The Bracket cannot be used with LDL2-33×8 Series.


Bracket **BK-LDQ2 Series**




This Bracket can be used to mount four Bar Light Units.

You can adjust the irradiation angle when you secure the Light Unit.

There are two types of Polarizing Plates. Use a combination of pairs when mounting with emission from four directions.



How to Recognize a Polarizing Plate Pair




A pair of Polarizing Plates will form a dark area when they are overlapped at a right angle. They will not form a dark area when overlapped in parallel.

Specifications of Options


Diffusion Plate		Polarizing Plate				Protective Plate		Separate Brackets		Integrated Brackets	
Direct number	Model	Direct number	Model	Direct number	Model	Direct number	Model	Direct number	Model	Direct number	Model
4001026	DF-LDL2-33X8	4001028	PL-LDL2-33X8-HO	4001029	PL-LDL2-33X8-VE	-	-	4000867	BK-LDL2	4001031	BK-LDQ2-33X8
4000840	DF-LDL2-41X16	4000847	PL-LDL2-41X16	4000888	PL-LDL2-41X16-VE	4000860	CV-LDL2-41X16			4000985	BK-LDQ2-41X16
4000841	DF-LDL2-80X16	4000848	PL-LDL2-80X16	4000889	PL-LDL2-80X16-VE	4000861	CV-LDL2-80X16			4000986	BK-LDQ2-80X16
4000842	DF-LDL2-119X16	4000849	PL-LDL2-119X16	4000890	PL-LDL2-119X16-VE	4000862	CV-LDL2-119X16			4000987	BK-LDQ2-119X16
4000843	DF-LDL2-74X30	4000850	PL-LDL2-74X30	4000891	PL-LDL2-74X30-VE	4000863	CV-LDL2-74X30			4000988	BK-LDQ2-74X30
4000844	DF-LDL2-146X30	4000854	PL-LDL2-146X30	4000892	PL-LDL2-146X30-VE	4000864	CV-LDL2-146X30			4000989	BK-LDQ2-146X30
4000845	DF-LDL2-218X30	4000851	PL-LDL2-218X30	4000893	PL-LDL2-218X30-VE	4000866	CV-LDL2-218X30			4000990	BK-LDQ2-218X30
4000846	DF-LDL2-266X30	4000853	PL-LDL2-266X30	4000894	PL-LDL2-266X30-VE	4000865	CV-LDL2-266X30			4000991	BK-LDQ2-266X30

Model Number Description

Diffusion Plates, Polarizing Plates, and Protective Plates



Separate Brackets




Integrated Brackets




Dimension Diagrams

DF/PL/CV-LDL2 Series


16-mm-wide Models



30-mm-wide Models




For the LDL2-33X8 Series




BK-LDL2 (for entire Series)

Bilaterally Symmetric



BK-LDQ2 Series


16-mm-wide Models and 30-mm-wide Models



Model	A	B	C
BK-LDQ2-41×16	108	70	60
BK-LDQ2-80×16	148	110	100
BK-LDQ2-119×16	186	148	138
BK-LDQ2-74×30	150	112	100
BK-LDQ2-146×30	222	184	172
BK-LDQ2-218×30	294	256	244
BK-LDQ2-266×30	342	304	292

BK-LDQ2-33×8

For the LDL2-33X8 Series



* Please contact a CCS sales representative for the dimension diagrams of special-order products.


Technical Data

Brightness Distribution

The wide models provide uniform illumination over a wide area. We recommend models with this new feature.


LWD=50mm

Shutter speed: 1/4,000 s Actual measurement of LDL2-266X30RD-WD
(The values are for reference only.)



LWD=100mm

Shutter speed: 1/2,000 s Actual measurement of LDL2-266X30RD-WD
(The values are for reference only.)



* Relative sensor brightness distribution measurement conditions: Intensity: 100%, Lens: F16, Width: 775 mm, Field of vision: 303 × 227 mm


* Brightness will vary based on the camera's spectral response. The values given here are for reference only. The values are for reference only.

Graphs of Temporal Changes


* There are virtually no changes in the graph values that result from the directional characteristics or whether optional products are mounted.

LDL2-41X16RD-WD (Red)

Temporal Changes in Temperature




Temporal Changes in Irradiation Output




LDL2-41X16SW-WD (White)

Temporal Changes in Temperature



Temporal Changes in Irradiation Output



* Graph measurement conditions: Actual measurement values for an intensity or 100% and an ambient air temperature or 20°C. (These values are for reference only.)

Product Lineup

Standard Product Selection Table

The standard models have eight sizes of light-emitting surface from a compact 33 mm × 8 mm to a wide 266 mm × 30 mm. Up to 61 models with different combinations of size, light color, and directional characteristics are available.

* Product Number Guide: You can easily access the information page for any of our products by entering the item's 7-digit product number in the designated box on the CCS website (image processing page).

		Direct number	Model	LED color	Light-emitting surface size	Input voltage	Power consumption	Weight	Supported Options	
Models with 8-mm-wide light-emitting surface	Wide type	1004646	LDL2-33×8RD	Red	33 x 8 mm	24 V	1.3 W	20 g	Diffusion Plate	DF-LDL2-33X8
		1004647	LDL2-33×8SW	White			0.8 W		Polarizing Plate	PL-LDL2-33X8-HO PL-LDL2-33X8-VE
		1004648	LDL2-33×8BL	Blue					Bracket	BK-LDQ2-33X8
		1004649	LDL2-33×8GR	Green						
		1004650	LDL2-33×8IR850	Infrared						
Models with 16-mm-wide Light-emitting Surface	Narrow type	1003702	LDL2-41X16RD	Red	41 x 16 mm	24 V	1.9 W	50 g	Diffusion Plate	DF-LDL2-41X16
		1003705	LDL2-41X16SW	White					Polarizing Plate	PL-LDL2-41X16 PL-LDL2-41X16-VE
		1003704	LDL2-41X16BL	Blue					Protective Plate	CV-LDL2-41X16
		1003703	LDL2-41X16GR	Green					Bracket	BK-LDQ2-41X16
		1003710	LDL2-80X16RD	Red	80 x 16 mm	24 V	3.8 W	75 g	Diffusion Plate	DF-LDL2-80X16
		1003713	LDL2-80X16SW	White					Polarizing Plate	PL-LDL2-80X16 PL-LDL2-80X16-VE
		1003712	LDL2-80X16BL	Blue					Protective Plate	CV-LDL2-80X16
		1003711	LDL2-80X16GR	Green					Bracket	BK-LDQ2-80X16
		1003718	LDL2-119X16RD	Red	119 x 16 mm	24 V	5.7 W	95 g	Diffusion Plate	DF-LDL2-119X16
		1003721	LDL2-119X16SW	White					Polarizing Plate	PL-LDL2-119X16 PL-LDL2-119X16-VE
		1003720	LDL2-119X16BL	Blue					Protective Plate	CV-LDL2-119X16
		1003719	LDL2-119X16GR	Green					Bracket	BK-LDQ2-119X16
	Wide type	1003706	LDL2-41X16RD-WD	Red	41 x 16 mm	24 V	1.9 W	50 g	Diffusion Plate	DF-LDL2-41X16
		1003709	LDL2-41X16SW-WD	White					Polarizing Plate	PL-LDL2-41X16 PL-LDL2-41X16-VE
		1003708	LDL2-41X16BL-WD	Blue					Protective Plate	CV-LDL2-41X16
		1003707	LDL2-41X16GR-WD	Green					Bracket	BK-LDQ2-41X16
		1003714	LDL2-80X16RD-WD	Red	80 x 16 mm	24 V	3.8 W	75 g	Diffusion Plate	DF-LDL2-80X16
		1003717	LDL2-80X16SW-WD	White					Polarizing Plate	PL-LDL2-80X16 PL-LDL2-80X16-VE
		1003716	LDL2-80X16BL-WD	Blue					Protective Plate	CV-LDL2-80X16
		1003715	LDL2-80X16GR-WD	Green					Bracket	BK-LDQ2-80X16
		1003722	LDL2-119X16RD-WD	Red	119 x 16 mm	24 V	5.7 W	95 g	Diffusion Plate	DF-LDL2-119X16
		1003725	LDL2-119X16SW-WD	White					Polarizing Plate	PL-LDL2-119X16 PL-LDL2-119X16-VE
		1003724	LDL2-119X16BL-WD	Blue					Protective Plate	CV-LDL2-119X16
		1003723	LDL2-119X16GR-WD	Green					Bracket	BK-LDQ2-119X16
Models with 30-mm-wide Light-emitting Surface	Narrow type	1003726	LDL2-74X30RD	Red	74 x 30 mm	24 V	5.7 W	100 g	Diffusion Plate	DF-LDL2-74X30
		1003729	LDL2-74X30SW	White					Polarizing Plate	PL-LDL2-74X30 PL-LDL2-74X30-VE
		1003728	LDL2-74X30BL	Blue					Protective Plate	CV-LDL2-74X30
		1003727	LDL2-74X30GR	Green					Bracket	BK-LDQ2-74X30
		1003734	LDL2-146X30RD	Red	146 x 30 mm	24 V	12 W	170 g	Diffusion Plate	DF-LDL2-146X30
		1003737	LDL2-146X30SW	White					Polarizing Plate	PL-LDL2-146X30 PL-LDL2-146X30-VE
		1003736	LDL2-146X30BL	Blue					Protective Plate	CV-LDL2-146X30
		1003735	LDL2-146X30GR	Green					Bracket	BK-LDQ2-146X30
		1003742	LDL2-218X30RD	Red	218 x 30 mm	24 V	18 W	240 g	Diffusion Plate	DF-LDL2-218X30
		1003745	LDL2-218X30SW	White					Polarizing Plate	PL-LDL2-218X30 PL-LDL2-218X30-VE
		1003744	LDL2-218X30BL	Blue					Protective Plate	CV-LDL2-218X30
		1003743	LDL2-218X30GR	Green					Bracket	BK-LDQ2-218X30
		1003750	LDL2-266X30RD	Red	266 x 30 mm	24 V	21 W	280 g	Diffusion Plate	DF-LDL2-266X30
		1003753	LDL2-266X30SW	White					Polarizing Plate	PL-LDL2-266X30 PL-LDL2-266X30-VE
		1003752	LDL2-266X30BL	Blue					Protective Plate	CV-LDL2-266X30
		1003751	LDL2-266X30GR	Green					Bracket	BK-LDQ2-266X30
	Wide type	1003730	LDL2-74X30RD-WD	Red	74 x 30 mm	24 V	5.7 W	100 g	Diffusion Plate	DF-LDL2-74X30
		1003733	LDL2-74X30SW-WD	White					Polarizing Plate	PL-LDL2-74X30 PL-LDL2-74X30-VE
		1003732	LDL2-74X30BL-WD	Blue					Protective Plate	CV-LDL2-74X30
		1003731	LDL2-74X30GR-WD	Green					Bracket	BK-LDQ2-74X30
		1003738	LDL2-146X30RD-WD	Red	146 x 30 mm	24 V	12 W	170 g	Diffusion Plate	DF-LDL2-146X30
		1003741	LDL2-146X30SW-WD	White					Polarizing Plate	PL-LDL2-146X30 PL-LDL2-146X30-VE
		1003740	LDL2-146X30BL-WD	Blue					Protective Plate	CV-LDL2-146X30
		1003739	LDL2-146X30GR-WD	Green					Bracket	BK-LDQ2-146X30
		1003746	LDL2-218X30RD-WD	Red	218 x 30 mm	24 V	18 W	240 g	Diffusion Plate	DF-LDL2-218X30
		1003749	LDL2-218X30SW-WD	White					Polarizing Plate	PL-LDL2-218X30 PL-LDL2-218X30-VE
		1003748	LDL2-218X30BL-WD	Blue					Protective Plate	CV-LDL2-218X30
		1003747	LDL2-218X30GR-WD	Green					Bracket	BK-LDQ2-218X30
		1003754	LDL2-266X30RD-WD	Red	266 x 30 mm	24 V	21 W	280 g	Diffusion Plate	DF-LDL2-266X30
		1003757	LDL2-266X30SW-WD	White					Polarizing Plate	PL-LDL2-266X30 PL-LDL2-266X30-VE
		1003756	LDL2-266X30BL-WD	Blue					Protective Plate	CV-LDL2-266X30
		1003755	LDL2-266X30GR-WD	Green					Bracket	BK-LDQ2-266X30

Custom Product Selection Table

Ten sizes of models with 16-mm-wide light-emitting surface areas and 17 sizes of models with 30-mm-wide light-emitting surface areas are available. Various combinations of light color and directional characteristics can be selected from a lineup of 216 models.

	Direct number	Model	LED color	Light-emitting surface size	Input voltage	Power consumption	Weight	Supported Options
Models with 16-mm-wide Light-emitting Surface	Narrow type	-	Red White Blue Green	158 x 16 mm	24 V	7.6 W	120 g	For details, please contact a CCS sales representative.
		-		197 x 16 mm	24 V	9.5 W	145 g	
		-		236 x 16 mm	24 V	12 W	170 g	
		-		275 x 16 mm	24 V	14 W	195 g	
		-		314 x 16 mm	24 V	16 W	220 g	
		-		353 x 16 mm	24 V	18 W	245 g	
		-		392 x 16 mm	24 V	19 W	270 g	
		-		431 x 16 mm	24 V	21 W	295 g	
		-		470 x 16 mm	24 V	23 W	320 g	
		-		509 x 16 mm	24 V	25 W	345 g	
	Wide type	-		158 x 16 mm	24 V	7.6 W	120 g	
		-		197 x 16 mm	24 V	9.5 W	145 g	
		-		236 x 16 mm	24 V	12 W	170 g	
		-		275 x 16 mm	24 V	14 W	195 g	
		-		314 x 16 mm	24 V	16 W	220 g	
		-		353 x 16 mm	24 V	18 W	245 g	
		-		392 x 16 mm	24 V	19 W	270 g	
		-		431 x 16 mm	24 V	21 W	295 g	
		-		470 x 16 mm	24 V	23 W	320 g	
		-		509 x 16 mm	24 V	25 W	345 g	
Models with 30-mm-wide Light-emitting Surface	Narrow type	-		LDL2-26X30	24 V	1.9 W	55 g	For details, please contact a CCS sales representative.
		-		LDL2-50X30	24 V	3.8 W	80 g	
		-		LDL2-98X30	24 V	7.6 W	125 g	
		-		LDL2-122X30	24 V	9.5 W	150 g	
		-		LDL2-170X30	24 V	14 W	200 g	
		-		LDL2-194X30	24 V	16 W	225 g	
		-		LDL2-242X30	24 V	19 W	275 g	
		-		LDL2-290X30	24 V	23 W	325 g	
		-		LDL2-314X30	24 V	25 W	350 g	
		-		LDL2-338X30	24 V	27 W	375 g	
		-		LDL2-362X30	24 V	29 W	400 g	
		-		LDL2-386X30	24 V	31 W	425 g	
		-		LDL2-410X30	24 V	33 W	450 g	
		-		LDL2-434X30	24 V	35 W	475 g	
		-		LDL2-458X30	24 V	37 W	500 g	
		-		LDL2-482X30	24 V	38 W	525 g	
		-		LDL2-506X30	24 V	40 W	550 g	
	Wide type	-		LDL2-26X30-WD	24 V	1.9 W	55 g	
		-		LDL2-50X30-WD	24 V	3.8 W	80 g	
		-		LDL2-98X30-WD	24 V	7.6 W	125 g	
		-		LDL2-122X30-WD	24 V	9.5 W	150 g	
		-		LDL2-170X30-WD	24 V	14 W	200 g	
		-		LDL2-194X30-WD	24 V	16 W	225 g	
		-		LDL2-242X30-WD	24 V	19 W	275 g	
		-		LDL2-290X30-WD	24 V	23 W	325 g	
		-		LDL2-314X30-WD	24 V	25 W	350 g	
		-		LDL2-338X30-WD	24 V	27 W	375 g	
		-		LDL2-362X30-WD	24 V	29 W	400 g	
		-		LDL2-386X30-WD	24 V	31 W	425 g	
		-		LDL2-410X30-WD	24 V	33 W	450 g	
		-		LDL2-434X30-WD	24 V	35 W	475 g	
		-		LDL2-458X30-WD	24 V	37 W	500 g	
		-		LDL2-482X30-WD	24 V	38 W	525 g	
		-		LDL2-506X30-WD	24 V	40 W	550 g	

Model Number
Description

LDL2- ○○X○○ □□ - △△

①

②


③

① Light-emitting surface size
33 × 8 to 506 × 30

② LED color
RD : Red
SW : White
BL : Blue
GR : Green
IR : Infrared (LDL2-33×8 only)




③ Directional Characteristics
None: Narrow type
(Wide type only for LDL2-33×8)
WD: Wide type

Common Specifications

LED color	Red (RD)	White (SW)	Blue (BL)	Green (GR)	Infrared (IR)
Input voltage (max.)	24 VDC				
Peak wavelength (typical)	635 nm	-	470 nm	525 nm	850 nm
Correlated color temperature (typical)	-	6600 K	-	-	-
Cable length	0.3 m				
Input connector	SMR-03V-B				
Polarity and signals	1: Anode (+), brown, 2: NC, 3: Cathode (-), blue				
Case material	Aluminum alloy				
Operating temperature and humidity	Temperature: 0 to 40°C, Humidity: 20% to 85% (with no condensation)				
Storage temperature and humidity	Temperature: -20 to 60°C, Humidity: 20% to 85% (with no condensation)				
Cooling method	Natural air cooling				
Spectral distribution	 * Use an R60-series Sharp-cut Filter for red light.				

* The values for irradiation strength that are given in this catalog are for reference only.

Dimension Diagrams

LDL2-nx16RD/SW/BL/GR (same for -WD models) <table border="1"> <thead> <tr> <th>Model</th><th>A</th><th>B</th></tr> </thead> <tbody> <tr> <td>LDL2-41×16</td><td>53</td><td>41</td></tr> <tr> <td>LDL2-80×16</td><td>92</td><td>80</td></tr> <tr> <td>LDL2-119×16</td><td>131</td><td>119</td></tr> </tbody> </table> n=B  Cable length: 300 mm	Model	A	B	LDL2-41×16	53	41	LDL2-80×16	92	80	LDL2-119×16	131	119	LDL2-nx30RD/SW/BL/GR (same for -WD models) <table border="1"> <thead> <tr> <th>Model</th><th>A</th><th>B</th></tr> </thead> <tbody> <tr> <td>LDL2-74×30</td><td>86</td><td>74</td></tr> <tr> <td>LDL2-146×30</td><td>158</td><td>146</td></tr> <tr> <td>LDL2-218×30</td><td>230</td><td>218</td></tr> <tr> <td>LDL2-266×30</td><td>278</td><td>266</td></tr> </tbody> </table> n=B  Cable length: 300 mm	Model	A	B	LDL2-74×30	86	74	LDL2-146×30	158	146	LDL2-218×30	230	218	LDL2-266×30	278	266	LDL2-33×8RD/BL/GR/SW/IR  Cable length: 300 mm
Model	A	B																											
LDL2-41×16	53	41																											
LDL2-80×16	92	80																											
LDL2-119×16	131	119																											
Model	A	B																											
LDL2-74×30	86	74																											
LDL2-146×30	158	146																											
LDL2-218×30	230	218																											
LDL2-266×30	278	266																											

* Please contact a CCS sales representative for the dimension diagrams of special-order products.

"LDL" is a trademark of CCS.

Precautions

- Carefully read the product's instruction manual before use to ensure correct operation.
- Product specifications and design are subject to change without notice.
- Examples of workpiece imaging in this catalog are a guide that may be informative for choosing Light Units. Please check the functions of the equipment and requirements before choosing a Light Unit.

CCS Inc.

Headquarters

Shimodachiuri-agaru, Karasuma-dori, Kamigyo-ku, Kyoto 602-8011 Japan

Phone: +81-75-415-8284 / Fax: +81-75-415-8278

URL: <http://www.ccs-grp.com> E-mail: intlsales@ccs-inc.co.jp

Copyright © 2011 CCS Inc. All Rights Reserved.
Descriptions in this catalog are based on information available as of March 2011. 02002-00-1103-LDL2 catalog