



CLASS	NOMINAL LENGTH						PERPENDICULARITY TOLERANCE	CLASS	NOMINAL LENGTH ON SHORTER SIDE			
	L ≤ 10	10 < L ≤ 30	30 < L ≤ 100	100 < L ≤ 300	300 < L ≤ 1000	1000 < L ≤ 3000			L ≤ 100	100 < L ≤ 300	300 < L ≤ 1000	1000 < L ≤ 3000
H	±0.02	±0.05	±0.1	±0.2	±0.3	±0.4	H	±0.2	±0.3	±0.4	±0.5	
K	±0.05	±0.1	±0.2	±0.4	±0.6	±0.8	K	±0.4	±0.6	±0.8	±1.0	

CLASS	NOMINAL LENGTH						PERPENDICULARITY TOLERANCE	CLASS	NOMINAL LENGTH ON SHORTER SIDE			
	L ≤ 10	10 < L ≤ 30	30 < L ≤ 100	100 < L ≤ 300	300 < L ≤ 1000	1000 < L ≤ 3000			L ≤ 100	100 < L ≤ 300	300 < L ≤ 1000	1000 < L ≤ 3000
H	±0.02	±0.05	±0.1	±0.2	±0.3	±0.4	H	±0.2	±0.3	±0.4	±0.5	
K	±0.05	±0.1	±0.2	±0.4	±0.6	±0.8	K	±0.4	±0.6	±0.8	±1.0	

OLD DRAWING NO.

1): DO NOT HOLD THIS AREA / 保持不可範囲

△x						FINISH	BLACK ANODIZING	UNIT:mm	
△x						SURFACE			
△x						MATERIAL	ALLUMINIUM ALLOY	MODEL NAME	MML5-HR80VI-43M58
△x	A-001	2023.May.29	NEW			CHAMFER		PART NAME	OUTLINE DRAWING
△x	MARK	COM-REV	DATE(YMD)	CHANGE	SIGNATURE	TOLERANCE CLASS		DRAWING NO.	A24686A0100101A-001
DESIGNED	Suzuki	DRAWN	Suzuki	CHECKED	モリテックス	SCALE	1:1	SHEET	1/1
				'23.05.31	柴田				
				'23.06.01	山中				

MAGNIFICATION : 5x  
EFFECTIVE Fno : 14.7 - 22