



## INDUSTRIAL/MACHINE VISION APPLICATIONS

# FLIR BLACKFLY<sup>®</sup> S

P/N BFS-U3-51S5PC

### ENABLE NEW APPLICATIONS WITH ON-SENSOR POLARIZATION

See the world in a whole new way with the FLIR Blackfly S.

Sony's Pregius sensors with on-sensor polarizing filters adds polarimetry to the FLIR Blackfly S already powerful feature-set. The USB 3.1 Gen 1 interface enables a global shutter readout at 75 FPS in a compact, low power package. This camera is ideal for building the next generation of polarimetry based industrial, traffic and UAS applications.

[www.flir.com/mv](http://www.flir.com/mv)

## FEATURES

### ON-SENSOR POLARIZING FILTERS

Enable new imaging possibilities using global shutter CMOS sensors with polarization. The Spinnaker SDK makes interpolation and analysis of polarization data easy.

### DEVELOP ONCE, DEPLOY ANYWHERE

Support for a wide range of operating systems and host system hardware architectures. Easily switch to board level models for embedded systems. Simplified product iteration with consistent form factor across sensor sizes.

### ACCELERATE APPLICATION DEVELOPMENT

Compatible with third party software and hardware. Less code-writing required using powerful on-camera features. Quickly build custom applications with rich sample code and descriptive API logging.

## APPLICATIONS

See through transparent and reflective materials including plastic, epoxy and glass by removing unwanted reflections

Inspect difficult-to-image materials such as protective films and clear-coat

Simplify training data for autonomous vehicles by eliminating unwanted glare

Dynamic removal of glare improves UAS and ITS system performance in uncontrolled and unpredictable lighting conditions



USB  
VISION

GEN<i>CAM

## SPECIFICATIONS

SPECS	BFS-U3-51S5P	BFS-U3-51S5PC
Resolution	2448 x 2048	
Frame Rate*	75 FPS	
Megapixels	5.0 MP	
Chroma	Polarized	Polarized Color
Sensor	Sony IMX250MZR, CMOS, 2/3"	Sony IMX250MYR, CMOS, 2/3"
Readout Method	Global shutter	
Pixel Size	3.45 µm	
Lens Mount	C-mount	
ADC	10-bit / 12-bit	
Minimum Frame Rate**	1 FPS	
Gain Range**	0 to 47 dB	
Exposure Range**	6 µs to 30 s	20 µs to 30 s
Acquisition Modes	Continuous, Single Frame, Multi Frame	
Partial Image Modes	Pixel binning, ROI	
Image Processing	Gamma	
Sequencer	Up to 8 sets using 6 features, including image size	
Image Buffer	240 MB	
User Sets	2 user configuration sets for custom camera settings	
Flash Memory	1 MB non-volatile memory	
Opto-isolated I/O	1 input, 1 output	
Non-isolated I/O	1 bi-directional	
Auxiliary Output	3.3 V, 150 mA maximum	
Serial Port	Supported	
Interface	USB 3.1 Gen 1	
Power Requirements	5 - 24 V via GPIO or 5 V via USB3 interface	
Power Consumption	3 W maximum	
Dimensions/Mass	29 mm x 29 mm x 30 mm / 36 g	
Machine Vision Standard	USB3 Vision v1.0	
Compliance	CE, FCC, KCC, RoHS, REACH. The ECCN for this product is: EAR099.	
Temperature	Operating: 0°C to 50°C Storage: -30°C to 60°C	
Humidity	Operating: 20% to 80% (no condensation) Storage: 30% to 95% (no condensation)	
Warranty	3 years	

\*Frame rates are measured with Device Link Throughput Limit of 500 MBps and Acquisition Frame Rate disabled. Values are rounded down to whole numbers.

\*\*Values are the same in binning and no binning modes.

### FLIR Integrated Imaging Solutions

#### CANADA

12051 Riverside Way  
Richmond, BC, Canada  
V6W 1K7  
T: +1 866.765.0827 (toll free)  
T: +1 604.242.9937  
F: +1 604.242.9938  
E: mv-sales@flir.com  
www.flir.com/mv

#### USA

T: +1 866.765.0827 (toll free)  
E: mv-na-sales@flir.com

#### EUROPE

T: +49 7141 488817-0  
F: +49 7141 488817-99  
E: mv-eusales@flir.com

#### CHINA

T: +86 10 8215 9938  
F: +86 10 8215 9936  
E: mv-chinasales@flir.com

#### ASIA

E: mv-asiasales@flir.com

www.flir.com  
NASDAQ: FLIR

©2019 FLIR® Integrated Imaging Solutions Inc. All rights reserved.  
Names and marks appearing on the products herein are either registered trademarks or trademarks of FLIR® Systems, Inc. and/or its subsidiaries. Specifications are subject to change without notice.

VN: BFS-U3-51S5PC-v2

FIND THE BEST BLACKFLY S  
FOR YOUR NEEDS



The World's Sixth Sense®